



# A Review On Performance Of Solar Pv-Powered Battery And D G Set Predicted Ev Battery Swapping Charging Station

Pratiksha Gawade 1<sup>st</sup>, Arati Sakat 2<sup>nd</sup>

Assistant Professor 1<sup>st</sup>, Assistant Professor 2<sup>nd</sup>

Department of Electrical Engg,

Sharadchandra Pawar College of Engineering and Technology, Someshwarnagar  
Pune, 412306, India

**Abstract:** A charging station for electric vehicles (CS) is equipped with a grid connection, a diesel generating set, a system for energy storage, a solar PV array, and a battery to ensure reliable charging in linked, coupled, and detached modes. This work encompasses the examination and evaluation of these methodologies. The primary purpose of the charging station is to store energy in batteries. This is achieved through the employment of a solar photovoltaic (PV) system and a battery energy storage (BES) system. In the event that the battery's energy is depleted or the solar array is unable to generate electricity, the charging infrastructure can intelligently utilize a DG (Diesel Generator) unit or the grid as alternative sources of power. The DG sets are engineered to maintain a steady operational level of 80-85% of the model in order to optimize fuel efficiency. Global environmental pollution is caused by the transportation sector's high carbon dioxide emissions. The use of electric vehicles (EVs) presents a fantastic chance to cut carbon emissions. Using a battery switching station (BSS) at battery charging stations allows electric vehicles to be powered more rapidly and efficiently (BCS). Switching Technology is the best way to complete an extensive statewide trip.

This essay examines the examination of electric vehicle performance in various electrical aspects, as well as the challenges and advantages of adopting them as a sensible step towards environmentally conscious and cost-effective transportation.

**Index Terms - Electric Vehicles, PV Array, Battery Swapping, Charging Station, Charging Modes, DG Set, Grid.**

## I. INTRODUCTION

Electric vehicles (EVs) are now considered to be highly efficient modes of transportation due to their little exhaust emissions. Due to the benefits they offer, a total of 3 million electric vehicles (EVs) have already been deployed on the streets, and it is projected that this number will reach 100 million by the year 2030. Nevertheless, implementing the suggested approach necessitates a significant quantity of electrical power and charging infrastructure. Moreover, EVs cannot be deemed environmentally benign unless the electricity needed to charge them is derived from renewable energy sources. However, the use of coal for electricity generation simply transfers emissions from vehicles to power plants, without actually reducing them. Utilizing renewable energy sources for electricity generation allows for the entire elimination of emissions, hence providing environmental benefits. Photovoltaic (PV) solar electricity is the most cost-effective and accessible form of renewable energy, suitable for both urban and rural areas. Some examples of renewable energy sources are solar systems, wind power, and hydro power with battery storage. In India, it is consistently and readily accessible. Wind and hydro energy rely on the local

environment, in contrast to solar photovoltaic systems. Wind energy is the optimal choice for coastal areas, whilst hydroelectricity is most advantageous in highland regions.

The most environmentally viable battery pack for charging stations is beneficial power. However, incorporating it into an existing battery charger introduces an extra energy transfer phase, which increases the complexity of the system and leads to energy loss. Each translation stage requires a dedicated controller that must incorporate the current control. Therefore, it is crucial to provide a comprehensive framework that can handle many modes and operations, requiring centralized management over all sources and effective coordination among them. The emergence of charging infrastructure fueled by renewable energy has garnered significant interest. Based on an extensive review of the literature, research on charging stations that use renewable energy has primarily focused on improving various charging aspects. These include the capacity of the storage facility, the driving force behind the charging process, the extent to which vehicles rely on renewable resources, the duration of the charging process, the associated costs, and the overall planning involved. Currently, only a limited number of newspapers have utilized the renewable energy charging station. Moreover, there is a lack of information regarding the efficiency of charging stations when the devices are being utilized. The literature mostly focuses on the efficacy of computer science employing The method of isolating power via electricity. The solar PV panel is only effective when it is connected to the network structure, as it requires a significant amount of sunlight (photovoltaic irradiance) to function. Similarly, the variability of sun irradiation poses challenges for photovoltaic generation in island mode. Consequently, a robust battery is necessary to counteract the impacts of fluctuating and impartial lighting. To prevent overcharging the battery, off the maximum power point tracking (MPPT) once it has reached full capacity. The transportation sectors globally cause significant harm to the environment through their substantial emissions of carbon dioxide. The adoption of electric vehicles (EVs) has the potential to significantly reduce carbon emissions. A battery switching station (BSS) enables electric vehicles to be charged more rapidly and efficiently at battery charging stations. Swapping Technology offers the optimal approach for completing a long interstate drive.

Consumers are attracted to electric cars due of its eco-friendly nature. These are environmentally beneficial because their combustion systems do not emit any harmful emissions. In addition, when consumers choose a zero-emission system, they not only reduce their environmental effect but also benefit from reduced maintenance requirements and potential eligibility for a tax credit. Several countries, notably the United States, China, Japan, and Germany, have modified their legislation and rules to promote the extensive adoption of electric vehicles (EVs). The performance of the Design for Power Storage Stations can effectively address the inherent issues of electric vehicles, including range anxiety and extended charging times. When the vehicle reaches a charging point, the depleted power supply is replaced with a fully charged one. Rapid charging decreases the duration required, however also exerts pressure on the battery, leading to a decrease in its overall lifespan. Battery shifting is crucial for maximizing battery life by charging the battery packs under optimal conditions.

### **There are fundamentally two approaches for replacing the battery:**

1. Robotic automation is the process of replacing battery packs without the need for human labor.
2. Manual way - This approach requires manually modifying depleted energy, which is more time-consuming compared to the prior method. Moreover, the involvement of labour is necessary for this procedure, so resulting in an escalation of the overall expenses. The paper presents the utilization of storage spaces and DG set-based CS. Under different operational conditions, it is imperative for the PV array to provide maximum energy. This system is capable of operating in three different modes: islanded, energy, and DG set-connected.

## **II. DIFFERENT TOPOLOGIES OF SYSTEM**

Electric vehicles (EVs) enhance energy efficiency in road transportation by eliminating the need for direct fuel burning and utilizing electricity, which is a highly versatile energy source. This contributes to the attainment of many transport policy objectives. When combined with a power production mix that has low carbon emissions, the advantages of this integration include increased energy security, improved air quality, reduced noise, and decreased greenhouse gas emissions. Moreover, as a prominent hub of innovation in the automotive sector, electric vehicles (EVs) possess significant potential to enhance industrial and economic competitiveness, as well as to attract investment and establish major markets. To

comprehensively investigate the factors that have influenced current patterns in electric mobility, the underlying dynamics driving their rapid growth, their effects on future adoption of electric vehicles, and the consequences for policy adaptations. [1]. India's renewable energy generation has experienced a two-fold rise since 2018, with onshore wind and solar photovoltaic (PV) being the main sources. The financial health of grid integration and distribution corporations, as forecasted in the previous year's projection, is hindering future expansion. The economic prospects for Latin America have been enhanced as a result of positive macroeconomic advancements in Brazil and successful auctions in Argentina. Supplementary wind and solar auctions enhance a more positive prediction. The maintenance of infrastructure in Sub-Saharan Africa (SSA) is contingent upon the availability of affordable finance and timely grid extension, which in turn determines the pace of implementation. The user's text is [2].

To establish a fully solar-powered electric vehicle (EV) charging network, particularly in an environmentally friendly community, the most effective approach is to address this construction challenge. The objective was to devise a technique for determining the optimal number of solar panels and the required amount of energy storage system (ESS) power to reduce costs connected with the development of a charging system, while still meeting the existing target for the average charging delay of an electric vehicle (EV). The simulation of solar radiation, which is the energy source for photovoltaic cells, is achieved by employing a discontinuous Markov chain model. This model is further modified to account for the presence of clouds in specific locations. The probability of a transition occurring between different solar radiation states is influenced by the frequency of fluctuations in cloudiness levels over a one-hour period. The methodology relies on a three-dimensional Markov chain model, wherein each state is determined by the level of solar radiation, the number of electric vehicles (EVs) in the system, and the state of charge of the energy storage system (ESS). The user's text is [3]. A 10kW three-port bidirectional converter enables direct DC charging for solar-powered electric vehicles (EVs). The converter that has been designed is compatible with the CCS and Chademo EV charging standards and may be utilized with a photovoltaic (PV) array that has a broad range of voltage and power. In order to enhance the frequency at which switching occurs and minimize losses in the converter, the utilization of integrated converters, silicon carbide (SiC) devices, and powdered alloy core inductors is implemented. As a result, there has been a significant increase in power density and a threefold reduction in voltage ripple at the EV and PV ports, in comparison to conventional systems. As part of the converter's modular design, a solar energy interleaved boost converter, an AC grid three-phase inverter, and an electric car interleaved flyback converter are all connected by a central DC-link with a voltage of 750V. This study demonstrates that, although flybacks are commonly believed to be appropriate mainly for low power applications, employing SiC devices in a QR mode flyback converter can achieve great efficiency even at high power levels. We have designed and evaluated three closed loop control systems for sub-converters, which facilitate the transfer of electricity between photovoltaic-electric vehicle, electric vehicle-grid, and photovoltaic-grid connections.




Fig.1 Green EV charging system in its entirety [3]

The user's text is [4]. Electric vehicles (EVs) and photovoltaic (PV) panel-based power resources are connected to the electrical network through a three-port integrated topology (TPIT). Compared to a typical topological structure, the suggested one has the potential to reduce the number of conversion operations. It also enables the exploration of new operating modes and control techniques, while ensuring the electrical grid's stability. The hardware that was developed includes energy converters and a digital control system. Additionally, methodologies for regulating the TPIT based on FBD electricity theory, predictive current management approaches, and [5] were proposed. This device features an integrated adapter for PV-Grid charging or power storage, along with a single-stage PV-Grid connection. This architectural design is suitable for implementing a centralized charging system in semi-commercial environments, such as a parking lot. To improve the use of string inverters in households, one can connect the charger side of the string inverter designs in series or parallel to distribute the current. The user's text is [6].

The energy storage control in a PV integrated EV charging station is managed using a self-adaptive hybrid optimization strategy that combines probabilistic and rule-based methods. The system is sufficiently flexible to accommodate variations in EV charging models and fluctuations in energy price patterns. The analysis determined that the proposed algorithm is unable to effectively handle the storage of power between the Energy Storage System (ESS) and the distribution grid while simultaneously meeting the statistical and uncoordinated charging needs of Electric Vehicles (EVs) on a continuous basis. Given the high cost of photovoltaic (PV) and energy storage systems (ESS), the study examines the amount of subsidies needed to economically deploy a PV system near a charging station for electric vehicles in combination with ESS. The operational expenses of an electric vehicle (EV) charging station can be reduced by strategically managing the distribution of loads throughout the course of the day and by considering the volatility of the power market. Implementing this strategy to deploy ESS will lead to significant cost savings in volatile markets. The user's text is [7]. A recent study was conducted to model and analyze a system that utilizes a 6.65 kW photovoltaic (PV) array near Galway, Ireland, to charge four electric vehicles. After doing simulations for a year, it was found that both AC and DC system designs were tested, and the DC system was determined to be 4.67% more efficient. The models modify power block efficiency in order to account for fluctuations in source and load conditions [8]. The study examined the relationship between the rate at which services are dropped and the choice of electric vehicle, as well as the performance of a dual-mode charging station modeled as a queuing network with many servers and different service rates. In order to minimize the occurrence of service interruptions at the charging station, it is necessary to develop an appropriate pricing framework that effectively manages and organizes electric vehicle charging operations. The simulation results [9] demonstrate the effectiveness of the proposed charge scheduling strategy. The feasibility of utilizing on-site wind energy from various buildings to power electric vehicles is being examined in relation to the provided information. Contemporary technology With the progress of technology, the task of installing and incorporating wind turbines onto buildings has become more convenient [10].

In order to comprehend the effects on the drivability and lifespan of electric vehicles (EVs), it is crucial to examine the Loss of Life (LoL) of EV batteries when employed as stationary energy storage (SES) in solar photovoltaic (PV) systems. This study studied the influence of several priority criteria,

specifically TCV2G and PCV2G, on the level of load loss (LoL) of electric vehicles (EVs) utilized as stationary energy storage (SES) in a typical solar photovoltaic (PV) system. An algorithm for power distribution in PCV2G has been developed, which prioritizes tasks based on their importance and considers power converter rectification. By prioritizing round robin EV IDs, state of charge (SOC), and energy provided, all electric vehicles (EVs) achieve a nearly equal level of loss of load (LoL). Moreover, the results of such an inquiry can be utilized to encourage electric vehicle (EV) purchasers to overlook their concerns about range and instead opt for vehicle-to-grid (V2G) services. The research can also be utilized to develop reliable algorithms for V2G dispatch and serve as a guide for using various sorts of features as priority criteria. The user's text is [11]. An efficient partnership between a WGenCO operating in the short-term electricity market and an EV aggregator involved in the power and associated service markets enhances the competitive advantage of the WGenCO and mitigates the risks associated with wind and EV energy imbalances. Figure 2 It became evident that there is a need to schedule wind power and electric vehicle (EV) demand coordination in the energy and regulation market using stochastic scheduling. The methodology has been evaluated on standard systems, including WGenCO without storage, WGenCO with energy storage devices, and an electrical system with synchronized EV-Wind energy exchange. The suggested approach was formulated utilizing model-based, optimal decision-making methodologies. In order to account for fluctuations in wind power generation, a Wind Generation Control Operator (WGenCO) has the option to choose between balancing, regulations, and/or Energy Storage System (ESS) services. The user's text is [12]. The paper introduces a method that utilizes the model predictive voltage and power (MPVP) technique to control the ac/dc interlinking converter in the battery energy preservation system. Additionally, a model predictive current and power (MPCP) technique is proposed for the management of the bidirectional dc-dc converter (BESS). The purpose of coordinating the dc/dc converter and the ac/dc converter is to regulate the dc and ac bus voltages and stabilize the outputs of renewable energy sources. An all-encompassing energy management strategy is implemented at the system level to guarantee consistent operation throughout a diverse range of operating modes. The performance of the proposed strategy is evaluated by using a PV-Wind-Battery combination with actual solar and wind characteristics. The evaluation shows that the recommended technique has better control capabilities and improved voltage quality compared to the conventional method [13]. The demonstration showcases the impact of strict feeder constraints on overall optimal performance. The issue of communicating requirements has been resolved. The program can be implemented utilizing communication infrastructures that have minimal bandwidth and support either unidirectional or bidirectional communication. This approach helps to minimize expenses related to deployment, operation, and maintenance, while also improving the reliability and scalability of the software. The application inherently ensures privacy by removing the identification data of the PEV. The user's text is [14]. The extent to which customers embrace electric vehicles will have a substantial impact on reducing detrimental emissions in the environment. There is currently a strong global inclination to distribute technology. The text is referenced by the number 15.



Fig.3 Battery Swapping Station

Based on the results, a charging station can produce high-quality voltage when utilized independently. Research on DG set linked operation has demonstrated that the ANC-based management algorithm can effectively maintain electrical contact with the grid under UPF or ideal DG set loading conditions. The user's text is [16]. Overseeing a solar photovoltaic (PV) system with battery storage technology that is

connected to the electrical grid. The system employs a variable control mechanism as it continuously checks the greatest attainable power point, battery charging and discharging, and grid current at a power factor of 1. This design and control strategy ensures the system's regulated power dynamics, which contribute to a reliable and uninterrupted supply of electricity to the grid. The control adapts its behavior based on environmental factors such as insufficient solar radiation and limited battery capacity, and regulates voltage accordingly. Management of the booster converter, grid and DC-link current, and regulation of battery voltage. The text is referenced by the number 17. An investigation was conducted on the multi-objective issue of optimal energy management employing renewable energy sources (RES) and demand response programs (DRPs). A revolutionary Multi-Objective Modified Tribe-PSO algorithm is being proposed. Another option. The grid-connected and stand-alone modes are examined separately to provide a clearer demonstration of the proposed approach. The number 18 is enclosed in square brackets. The main contributions to the research literature on smart home operation included the findings of a collaborative evaluation of dynamic price and peak power limiting-based demand response methods, a decentralized small-scale renewable energy system for future generations, the capabilities of electric vehicles for vehicle-to-home and vehicle-to-grid interactions, the two-way energy trading of an electric vehicle using the vehicle-to-grid option, and energy storage systems. The structures were built utilizing a HEM structural model based on a MILP framework. Net metering facilitates bidirectional electricity exchange. The energy that is returned to the grid is anticipated to be reimbursed at a predetermined rate, while the energy acquired from the grid is billed in real-time.

The study analysis was based on two essential ideas. Prior to the commencement of the offline optimization session, it is essential to have a comprehensive understanding of the real-time pricing signals. Moreover, it is presumed that there is a precise comprehension of consumer interests and purchase patterns. Data obtained from a solar power plant and a standard Portuguese family home with four occupants were employed. Multiple test cases were analyzed. An investigation was conducted to assess the effects of implementing a second disaster recovery plan that focuses on lowering peak power use. In the default scenario, it was believed that consumers were enthusiastic about charging their electric vehicles (EVs) immediately upon returning home and did not possess a Home Energy Management (HEM) system or an Energy Storage System (ESS). Compared to the baseline condition, which is similarly linked to the most costly everyday processes, the proposed technique achieved a higher level of efficiency by reducing power expenses by around 65%. The implementation of a HEM system allows for more efficient utilization of electricity by leveraging advanced technology. [19].

An all-encompassing framework for the management of electric vehicle charging and discharging. Knowledge exchange between HEMS (Helicopter Emergency Medical Services) and GEMS (Ground Emergency Medical Services) forms the foundation for coordination. The proposed system utilizes interchange information and day-ahead expected power profiles to create a daily plan for charging and discharging electric vehicles (EVs). The text is referenced by the number 20. This ensures an ample amount of available capacity to charge the limited photovoltaic (PV) system throughout the day, while also providing the ability to charge the electric vehicle (EV) for planned transit.

This research highlights the importance of synchronized management between photovoltaic (PV) storage and plug-in electric vehicle (PEV) storage in order to reduce the overall cost of obtaining power from the grid for a residential system. In order to evaluate different control strategies, the system takes into consideration the unpredictability of PV generation and load needs. The Cholesky reduction technique is employed to construct future possibilities, while also considering the link between these two uncertain elements. In order to maintain a consistent amount of PEV charging for the next day according to the owner's wishes and prevent PEV discharge during low-demand hours, fines are incorporated into the model's objective functionality. Subsequently, the SDDP algorithm is employed to resolve the optimization problem in the presence of uncertainty. By regulating the charge and discharge properties of both storage components, SDDP, the decision-maker, has the ability to minimize the overall costs for the customer. The number 21 is enclosed in square brackets. The economical and ecological impacts of integrating a photovoltaic (PV) array with diesel-electric power networks in rural regions MATLAB Simulink is employed to integrate load and demand, and allocate electricity output between the PV and diesel generators. The economic aspect of the model calculates the quantity of fuel consumed, the rate of kilowatt-hours produced per gallon of gasoline

supplied, and the overall fuel expenditure. The environmental module of the model computes the amount of CO<sub>2</sub>, particulate matter (PM), and x that are released into the atmosphere. The user's text is [22].

A multitasking management strategy for grid-connected inverters utilized in distributed generation (DG) systems (GCIs). The single-phase H-bridge voltage source inverter functions as the electrical connection between the DG system and the grid. To achieve the required active power injection into the grid, the recommended control algorithm operates the GCI in current control mode. The suggested control algorithm improves power quality by reducing current harmonics, compensating for reactive power, and injecting active power. The control algorithm enhances power quality by exclusively utilizing the remaining capacity of the GCI. The suggested control technique leverages a current breakdown framework that employs numerous adaptive noise cancellation (ANC) filters to extract the harmonic and reactive currents of the local loads. The extracted harmonics are utilized to calculate the compensatory currents that the GCI will introduce. The GCI was synchronized at the fundamental frequency by employing a single-phase phase-locked loop (PLL) and active noise cancellation (ANC) filtration devices. This control mechanism is designed to withstand grid voltage abnormalities and accommodate variations in grid frequency.

### III. CONCLUSION:-

This study examines the efficiency of batteries powered by solar photovoltaic (PV) systems, as well as the projected performance of electric vehicle (EV) battery swapping charging stations. Now, it is possible to create and utilize an electric vehicle (EV) charging system by incorporating solar power plants, battery banks, grids, and DG set-based CS. The objective of this study is to identify an effective solution to the existing deficiencies. This article contains examples of prior research, approaches, and advancements. The article explores the advantages and disadvantages of using electric vehicles for transportation, as well as their role in advancing more efficient, eco-friendly, and sustainable transportation.

### REFERENCES

- [1] Global EV Outlook 2018- Towards Cross-Modal Electrification, International Energy Agency. [Online] obtainable at: /download/direct/1045?fileName=Global EV Outlook 2018.pdf on the IAEA website.
- [2] InternationalEnergyAgency,"Renewables:AnalysisandForecasts through 2023," [Online]. English-Renewables- 2018ES.pdf is accessible at <https://webstore.iea.org/download/summary/2312>.
- [3] Optimal Capacity Sizing for Completely Green Charging Systems for Electric Vehicles," J. Ugirumurera and Z. J. Haas, IEEE Trans. Transport. Electrification, vol. 3, no. 3, September 2017, pp. 565-577.
- [4] A 10 kW Solar-Powered Bidirectional EV Charger Compatible With Chademo and COMBO," IEEE Trans, Power Electron., vol. 34, no. 2, pp. 1082-1098, Feb. 2019. G. R. ChandraMouli,J.Schijffelen,M.vandenHeuvel,M.Kardolus, and P. Bauer.
- [5] "Experimental Validation of a Three-Port Integrated Topology to Interface Electric Vehicles and Renewables With the Electrical Grid," V. Monteiro, J. G. Pinto, and J.L. Afonso, IEEETransactionsonIndustrialInformatics,vol.14,no.6,June 2018, pp. 2364–2374.
- [6] "Modeling, Design, Control, and Implementation of a Modified Z-Source Integrated PV/Grid/EV DC Charger/Inverter,"IEEETrans.Ind.Electron.,vol.65,no.6,pp.52135220,June2018
- [7] .S.A.Singh,G.Carli,N.A.Azeez, and S.S. Williamson."Hybrid Optimization for Economic Deployment of ESS in PV-Integrated EV Charging Stations," IEEE Trans. Ind. Informat.,vol.14,no.1,pp.106-116,Jan.2018.K.Chaudhari,A.Ukil,K.N.Kumar,U.Manandhar,andS.K.Kollimalla.
- [8] "Modeling and design of electric car charging systems that integrateon-siterenewableenergysources,"F.KineavyandM. Duffy,IEEE5thInternationalSymposiumonPower Electronics forDistributedGenerationSystems(PEDG),Galway,2014,pp. 1-8.
- [9] "Optimal Charging Scheduling by Pricing for EV Charging Station With Dual Charging Modes," IEEE Trans. Intelligent Transportat. Syst., 20(9), 3386-3396, Sept. 2019. Y. Zhang, P. You, and L. Cai.
- [10] "DistributedCoordinationofEVChargingWithRenewable Energy in a Microgrid of Buildings,"

IEEE Trans. Smart Grid, vol.9,no.6,pp.6253-6264,Nov.2018.Y.Yang,Q.Jia,G.Deconinck,X.Guan,Z.Qiu, andZ.Hu.

[11] "Loss-of-life investigation of EV batteries used as smart energystorageforcommercialbuilding-basedsolarphotovoltaic systems," N. K. Kandasamy, K. Kandasamy and K. J. Tseng, IETElectricalSystemsinTransportation,vol.7,no.3,pp. 223- 229, 9 2017.

[12] "Energy Exchange Between Electric Vehicle Load and WindGeneratingUtilities,"IEEETrans.PowerSys.,vol.31,no. 2, pp. 1248–1258, 2016. A. Tavakoli, M. Negnevitsky, D. T. Nguyen, and K. M. Muttaqi.

[13] "Model Predictive Control of Bidirectional DC-DC ConvertersandAC/DCInterlinkingConverters-A NewControl MethodforPV-Wind-BatteryMicrogrids,"byY.Shan,J.Hu,K. W. Chan, Q. Fu, and J. M. Guerrero Early Access to IEEE Trans. Sustain. Energy.

[14] "Decentralized PEV charging coordination to absorb extra wind energy using stochastically staggered dual-tariff schemes

[15] considering feeder-level restrictions," IET Gene., Trans. &Distri., vol. 12, no. 15, pp. 3655-3665, 28 August 2018.

[16] "Battery Swapping Technology,"2020 5th IEEE International Conference on Recent Advances and Innovations in Engineering(ICRAIE),2020, pp.1-4,S.Jain,Z.Ahmad,M. S.AlamandY.Rafat,"Implementation of SolarPV-BatteryandDieselGenerator Based Electric Vehicle Charging Station," IEEE Int. Conf. Power Electronics, Drives and Energy Systems (PEDES), Chennai,India,2018,pp.1-6.B.Singh,A.Verma,A.Chandra, and K. Al-Haddad

[17] "Integration of solar PVwith battery to single-phasegrid," IETGeneration,Transmission&Distribution,vol.11,no.8,pp. 2003-2012, 1 June 2017. N. Saxena, B. Singh, and A. L. Vyas.

[18] "Comparative assessment of two alternative modes multi- objective optimum power management of micro-grid: grid- connected and stand-alone," by H. Razmi and H. Doagou- Mojarad.IETRenewable Power Generation, 2019, volume13, issue 6, pages 802–815

[19] "Smart Household Operation Considering Bi-Directional EVandESSUtilizationbyReal-TimePricing-BasedDR,"byO.Erdinc,N.G.Paterakis,T.D.P.Mendes,A.G.Bakirtzis,andJ.P.S.CataloIEEETrans.SmartGrid ,May2015,volume6,issue 3, pages 1281–1291.

[20] "Electric Vehicle Charge-Discharge Management for Utilization of Photovoltaic by Coordination between Home and Grid Energy Management Systems,"by Yu Fujimoto, H. Asano, Y. Hayashi, A. Kawashima, S. Inagaki, and T. Suzuki Smart Grid, Early Access, IEEE Trans.

[21] "Coordinated Control of PEV and PV-based Storages in Residential System under Generation and Load Uncertainties", IEEE Trans. Ind. Applica., Early Access, F. Hafiz, A. R. de Queiroz, and I. Husain.

[22] "Simulink model foreconomic analysis and environmental consequences of a PV with diesel-battery system for remote communities," IEEE Trans. Power Systems, vol. 20, no. 2, pp. 692-700,May2005.R.W.Wies,R.A.Johnson,A.N.Agrawal, and T. J. Chubb.

[23] "Battery Swapping Technology", IEEE Trans. Mohammad Saad Alam Department of Electrical Engineering Aligarh Muslim University Aligarh, India saad.alam@zhcet.ac