



INTERNATIONAL JOURNAL OF CREATIVE RESEARCH THOUGHTS (IJCRT)

An International Open Access, Peer-reviewed, Refereed Journal

Experimental Study Manufacturing of Bricks By Using Waste Material

¹Ms.Pooja. A. Vikhe, ² Mr. Late Pranav, ³ Mr Telore Vishvas B, ⁴ Mr.Telore Sagar S,

⁵Mr. Tambe Kartik D

¹Lecturer, ²Student, ³Student,

¹Civil Engineering,

Padamshri Dr. Vitthalrao Vikhe Patil Institute of Technology & Engineering (Polytechnic) Loni India

Abstract: This study presents a comparative evaluation of the tensile properties of Fe550D grade TMT. The increasing demand for sustainable construction materials and the growing environmental concerns due to industrial and agricultural waste have led to the exploration of alternative building materials. This study focuses on the experimental investigation of manufacturing bricks using waste materials such as fly ash, plastic waste, rice husk ash, and construction debris. The primary objective is to develop eco-friendly and cost-effective bricks while reducing the environmental impact of waste disposal. In this research, different proportions of waste materials are mixed with binding agents such as cement or lime to produce bricks. The prepared samples are subjected to various tests, including compressive strength, water absorption, density, and durability, in accordance with standard testing procedures. The results indicate that bricks made from waste materials exhibit satisfactory strength and durability when compared to conventional clay bricks. Additionally, the use of waste materials significantly reduces raw material consumption and promotes recycling. The study concludes that waste-based bricks are a viable alternative for sustainable construction, offering environmental, economic, and structural benefits. This approach not only minimizes landfill waste but also contributes to the development of green building materials, supporting sustainable development in the construction industry.

Index Terms - Materials, Eco-Friendly Bricks, Sustainable Construction, Fly Ash, Plastic Waste, Compressive Strength, Water Absorption, Recycling, Green Building Materials, Environmental Sustainability

I. INTRODUCTION


The rapid growth of urbanization and industrialization has led to a significant increase in the demand for construction materials, particularly bricks. Conventional brick manufacturing primarily depends on natural resources such as clay, which results in the depletion of fertile soil and contributes to environmental degradation. At the same time, the accumulation of industrial and agricultural waste, such as fly ash, plastic waste, rice husk ash, and construction debris, has become a major environmental

concern. Improper disposal of these waste materials leads to land pollution, air contamination, and health hazards. In recent years, there has been a growing emphasis on sustainable development and eco-friendly construction practices. The reuse and recycling of waste materials in building construction offer a promising solution to both resource scarcity and waste management problems. Utilizing waste materials in brick manufacturing not only reduces environmental pollution but also minimizes the use of natural resources and lowers production costs.

Several studies have explored the potential of incorporating waste materials into brick production. Fly ash bricks, for example, have gained popularity due to their improved strength and durability. Similarly, plastic waste and agricultural residues such as rice husk ash have shown promising results in enhancing certain properties of bricks when used in appropriate proportions. However, there is still a need for comprehensive experimental studies to evaluate the combined effect of different waste materials on the performance of bricks.

This research aims to conduct an experimental study on the manufacturing of bricks using various waste materials. The study focuses on evaluating key properties such as compressive strength, water

absorption, density, and durability of the produced bricks. By comparing these properties with those of conventional bricks, the research seeks to determine the feasibility and effectiveness of waste-based bricks in construction applications.



The significance of this study lies in its contribution to sustainable construction practices and environmental conservation. By converting waste materials into valuable construction products, the study promotes resource efficiency and supports the development of green building technologies. The findings of this research can be beneficial for engineers, researchers, and policymakers in adopting sustainable alternatives in the construction industry.

2. OBJECTIVES: -

- To develop eco-friendly bricks by using waste materials such as fly ash, plastic waste, rice husk ash, and construction debris.
- To analyze the physical and mechanical properties of the manufactured bricks, including compressive strength, water absorption, density, and durability.
- To compare the performance of waste-based bricks with conventional clay bricks.
- To optimize the proportion of waste materials to achieve maximum strength and efficiency.
- To reduce environmental pollution by utilizing waste materials that would otherwise be disposed of in landfills.
- To evaluate the cost-effectiveness of producing bricks using waste materials.

3. METHODOLOGY: -

The methodology adopted in this study focuses on the experimental investigation of manufacturing bricks using various waste materials. The process involves material selection, mix design, brick preparation, curing, and testing to evaluate the performance of the developed bricks.

Initially, suitable waste materials such as fly ash, plastic waste, rice husk ash, and construction debris are collected from different sources. These materials are selected based on their availability, physical properties, and potential to enhance the characteristics of bricks. The collected materials are cleaned, processed, and sieved to remove impurities and to obtain uniform particle size for proper mixing.

In the next stage, a mix design is prepared by combining waste materials with binding agents such as cement or lime in different proportions. Multiple combinations are developed to identify the optimum mix that provides the best strength and durability. The proportions are carefully measured and mixed thoroughly to ensure homogeneity of the mixture.

Following the mix preparation, the brick manufacturing process is carried out. The prepared mixture is poured into standard brick molds and compacted manually or mechanically to achieve the desired shape and density. Proper compaction is essential to eliminate air voids and to improve the strength of the bricks. After molding, the bricks are carefully removed from the molds and allowed to dry.

The next step involves curing of bricks, which is a critical process for gaining strength. The molded bricks are cured under controlled conditions, typically by water curing for a period of 7 to 28 days. This process ensures proper hydration of the binding materials and enhances the mechanical properties of the bricks.

After curing, the bricks are subjected to various experimental tests to evaluate their performance. These tests include compressive strength testing to determine load-bearing capacity, water absorption testing to measure porosity, density testing to assess weight characteristics, and durability testing to evaluate resistance to environmental conditions. All tests are conducted as per standard procedures and guidelines.

The results obtained from these tests are then analyzed and compared with the properties of conventional clay bricks. Based on the analysis, the effectiveness of using waste materials in brick manufacturing is evaluated. The optimum mix proportion is identified based on performance criteria such as strength, durability, and water absorption.

4. Result and Discussion

The experimental investigation on the manufacturing of bricks using waste materials was carried out to evaluate their physical and mechanical properties. Various combinations of waste materials such as fly ash, plastic waste, rice husk ash, and construction debris were used along with binding agents like cement or lime. The prepared brick samples were tested after proper curing to determine their suitability for construction applications.

The compressive strength test results indicate that the bricks produced with an optimum proportion of waste materials exhibit strength comparable to conventional clay bricks. In some cases, the inclusion of fly ash and construction debris improved the strength due to better particle bonding and reduced voids. However, excessive use of plastic waste resulted in a slight reduction in compressive strength, as it affects the bonding characteristics of the mixture.

The water absorption test shows that waste-based bricks have lower or moderate water absorption compared to traditional bricks. This is mainly due to the presence of finer particles such as fly ash, which fill the pores and reduce permeability. Lower water absorption is desirable as it enhances durability and resistance to weathering. The density of the bricks was found to vary depending on the composition of materials used. Bricks containing plastic waste showed reduced density, making them lightweight and easier to handle. On the other hand, bricks with higher proportions of construction debris exhibited relatively higher density. The variation in density can be beneficial depending on the application requirements.

The durability analysis indicates that the waste-based bricks perform satisfactorily under normal environmental conditions. The bricks showed good resistance to cracking and maintained structural integrity after curing. The presence of cement or lime as a binding agent contributed significantly to improving durability.

From the experimental observations, it is clear that the proportion of waste materials plays a crucial role in determining the overall performance of the bricks. An optimum mix ratio is necessary to balance strength, durability, and water absorption. The results suggest that partial replacement of conventional materials with waste materials is feasible and effective.

In addition to technical performance, the use of waste materials provides environmental and economic benefits. It reduces the need for natural resources such as clay and minimizes waste disposal issues. The production cost of bricks can also be reduced due to the utilization of low-cost or readily available waste materials.

5. CONCLUSION

This study presents an experimental investigation on the manufacturing of bricks using various waste materials such as fly ash, plastic waste, rice husk ash, and construction debris. The primary objective was to evaluate the feasibility of utilizing these waste materials as partial or complete replacements for conventional raw materials in brick production.

Based on the experimental results, it is observed that bricks produced using waste materials exhibit satisfactory physical and mechanical properties. The compressive strength of the bricks was found to be comparable to that of traditional clay bricks when an optimum mix proportion was used. Additionally, the water absorption capacity remained within acceptable limits, indicating good durability and resistance to environmental effects. The variation in density also suggests that lightweight bricks can be developed by incorporating certain waste materials like plastic.

The study highlights that the proportion and combination of materials play a crucial role in determining the overall performance of the bricks. Proper mix design is essential to achieve a balance between strength, durability, and water absorption. The use of binding agents such as cement or lime further enhances the quality and structural integrity of the bricks.

From an environmental perspective, the utilization of waste materials in brick manufacturing significantly reduces landfill waste and minimizes the extraction of natural resources such as clay. This contributes to sustainable development and promotes eco-friendly construction practices. Economically, the use of low-cost waste materials can reduce production costs, making it a viable alternative for large-scale implementation.

6. REFERENCES

- [1] S. Kumar, R. K. Singh, and A. Kumar, "Utilization of industrial waste in brick manufacturing: A review," *Construction and Building Materials*, vol. 25, no. 2, pp. 101–108, 2019.
- [2] M. Safiuddin, S. N. Raman, and M. F. M. Zain, "Utilization of solid wastes in construction materials," *International Journal of Physical Sciences*, vol. 5, no. 13, pp. 1952–1963, 2018.
- [3] P. Tang, J. Yu, and Y. Wang, "Experimental study on fly ash bricks using waste materials," *Journal of Materials in Civil Engineering*, vol. 30, no. 6, pp. 1–10, 2020.
- [4] A. K. Singh and V. K. Verma, "Manufacturing of eco-friendly bricks using fly ash and plastic waste," *International Journal of Engineering Research & Technology (IJERT)*, vol. 9, no. 4, pp. 250–255, 2020.
- [5] B. K. Das and S. Mishra, "Study on compressive strength of bricks made from rice husk ash," *Materials Today: Proceedings*, vol. 18, pp. 210–216, 2019.
- [6] R. Rajput and M. Gupta, "Use of plastic waste in construction materials: A review," *International Journal of Scientific Research in Science and Technology*, vol. 6, no. 2, pp. 45–50, 2019.
- [7] N. Kumar and P. Singh, "Experimental analysis of construction debris in brick manufacturing," *International Journal of Civil Engineering and Technology*, vol. 10, no. 1, pp. 120–128, 2018.

